

## **TechDataSheet**

# MULTI UNDERBODY PROTECTION WAX TRANSLUCENT SPRAY

#### **Features**

- protects and maintains body and metal parts
- fast-drying duroplastic protective film
- very good adhesion
- heat-resistant up to +200°C
- · moisture displacing
- extremely well suited for protection and post-conservation
- flexible and slightly tacky wax layer with excellent temperature resistance
- · will not crack or become brittle
- · outstanding ability to penetrate
- · very good heat resistance and good flexibility when cold
- · resistant to water, salt spray, oil as well as diluted acids and bases

## **Areas of application**

PETEC Multi underbody protection wax offers ideal anti-corrosion and anti-stone chip protection properties in corrosion-prone areas and bonds to many surfaces. Thanks to its outstanding ability to penetrate, Multi underbody protection wax can also reach hard-to-reach cavities in the vehicle body.

#### **TechnicalData**

Base	paraffin wax
Base	Oil
Colours	Translucent
Curing	2 hours at 500 μm
Shelf life	36 Months
Salt spray test	1,000 at 100 μm (Ri0)
Temperature Resistance	-35 - +200

## **Usage Instructions**

Application temperature: +5°C to +30°C. Shake well before use. Spray PETEC Multi underbody protection wax from a distance of approx. 25 cm onto the rust-free, dry and degreased surface. For thicker layers, we recommend to let the product dry, befor applying the next layer. Applying multiple coatings may cause white colouration of the wax. Check on beforehand if the materials are compatible. Danger of autoxidation on alloys. The product contains solvents which may dissolve or attack existing coatings. Different underbody protection products should therefore not be combined with each other without conducting your own tests first.

Always conduct your own tests to ensure that the product is suitable for each application. Cannot be re-coated. Do not apply on the brake and exhaust system, heat plates or rubber parts. After use, turn the can upside down and spray until the valve is empty. Read the safety and technical data sheet!

(Download the PETEC data sheets at www.petec.de)

LiabilityClauseText



# **TechDataSheet**

# **Package Sizes**

PETEC MULTI UBS WAX Condition TRAISUCENT    I about a first   I ab	PETEC WITTUBS WIX GENERAL TRANSPORTER TRANSPORTER TRANSPORTER TO BE ARREST TO BE AR
Item no.: 73410	Item no.: 73450
1000 ml	500 ml

LiabilityClauseText