

WINDOW & BODY SEALANT, WHITE

Features

Window & body sealant with long lasting adhesion properties made of butyl rubber for permanent sealing of front, rear, and side windows, body and attached parts.

- permanent sealing of various materials
- permanently adhesive, does not harden
- can be dabbed off with itself
- for sealing of large surfaces
- equalises tensions in the body
- reliably prevents the infiltration of moisture, dirt and draught
- Resistant to water, salt water, as well as diluted acids and alkaline solutions

Areas of application

Can be used for sealing structures, highly-stressed joints and vibrating parts in body and container construction. For applications in the automotive, caravan, marine, construction and agricultural machinery sectors, as well as in industry and the trades.

TechnicalData

Base	butyl rubber
Colours	white
Shelf life	24 Months
Temperature Resistance	-30 - +80

Usage Instructions

Application temperature: +5°C to +40°C. Thoroughly clean and degrease sealing surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Cut open the cartridge above the thread, cut the nozzle as needed and screw it on the cartridge. Apply a layer with the desired thickness on one side using an applicator gun, adjust and fix the parts if necessary. Surplus material must be dabbed off with itself after drying. Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes

	
Item no.: 83300	Item no.: 83290
310 ml	310 ml