

WINDOW & BODY SEALANT, BLACK

Features

Long-lasting adhesion of windows & body sealants made of butyl rubber for permanent sealing of front, rear, and side windows, body and attached parts.

- permanent sealing of many materials
- permanently adhesive, does not harden
- can be dabbed off with itself
- for large-area sealing applications
- balances tensions within the body
- reliably prevents the infiltration of moisture, dirt and draught
- resistant to water, salt water, as well as diluted acids and alkaline solutions

Areas of application

Can be used for sealing structures, highly-stressed joints and vibrating parts in body and container construction. For applications in the automotive, caravan, marine, construction and agricultural machinery sector, as well as in industry and trade.

TechnicalData

Base	butyl rubber
Colours	black
Shelf life	24 Months
Temperature Resistance	-30 - +80

Usage Instructions

Application temperature: +5°C to +40°C. Thoroughly clean and degrease sealing surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Cut open the cartridge above the thread, cut the nozzle and screw on. Apply a layer with the desired thickness on one side using an applicator gun, adjust and fix the parts if necessary. Surplus material must be dabbed off with itself after drying. Check on beforehand if the materials are compatible. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet! (Download the PETEC data sheets at www.petec.de)

Package Sizes

	
<p>Item no.: 83300</p>	<p>Item no.: 83290</p>
<p>310 ml</p>	<p>310 ml</p>