

TechDataSheet

ASSEMBLY TAPE, CLEAR

Features

Double-sided high performance adhesive tape for clear and very strong adhesive bonds.

- · very high immediate adhesive strength
- good temperature resistance
- moisture resistant
- · reduces vibration
- · bridges gaps
- · can replace screws and rivets
- for indoor and outdoor applications
- good UV-resistance

Areas of application

Good adhesion to many materials such as metal, glass, stone, tiles, wood and different plastics. For fastening trim strips, profiles, reinforcement pieces, emblems, rear-view mirrors, signs and license plates.

TechnicalData

Colours	clear
Shelf life	36 Months
Shear force	7
Temperature Resistance	-40 - +100
Tensile strength	47 N /25 mm

Usage Instructions

Application temperature +5°C to +35°C. Thoroughly clean and degrease surface with PETEC Multi Cleaner (item no. 82100 or 82200). Stick the assembly tape to one of the surfaces to be bonded. Then remove the red protective foil and bond to the intended area, pressing firmly. In-house testing and suitability testing is required given the numerous applications, materials and other influencing factors. Read the technical data sheet. (Download the PETEC data sheets at www.petec.de)



TechDataSheet

Package Sizes



Item no.: 87192

2 m x 19 mm x 0.2 mm blister pack

LiabilityClauseText