

FOAM ASSEMBLY TAPE

Features

Double-sided adhesive tape, especially for hard-to-bond plastics such as PP, PE.

- extremely strong initial adhesion and adhesive strength
- extremely good adhesion to many materials
- long-lasting bonding
- gap bridging and vibration-absorbent
- suitable for all non-porous surfaces
- can replace screws and rivets
- can be used indoors and outdoors

Areas of application

For bonding and assembling of low-energy plastics such as PE, PP, PTFE, PBT, PA, PC, POM, PVA, PMMA, ABS, PBT, PVF, EPDM, PU, TPE PVC, A-PET, as well as mixed plastics and many more. Also for bonding material combinations, e.g. various plastics, metals, alloys, powder coatings, rubber, glass, stone, wood and many more.

TechnicalData

| | |
|------------------------|-------------|
| Colours | black |
| Shelf life | 36 Months |
| Shear force | 55 |
| Temperature Resistance | -40 - +120 |
| Tensile strength | 55 N /25 mm |

Usage Instructions

Application temperature +5°C to +35°C. Thoroughly clean and degrease surface with PETEC Multi Cleaner (item no. 82100 or 82200). Affix the assembly tape on one of the surfaces to be bonded. Then remove the blue protective film and bond to the intended location, pressing firmly. Always conduct your own tests to ensure that the product is suitable for each application. Read the technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes



Item no.: 87210

10 m x 19 mm x 1.1 mm blister
pack