

INSULATING AND ACOUSTIC PANEL

Features

Flexible, bitumen-based, noise reduction panel with self-adhesive backing to one side, to remove and reduce sound and noises on the bodywork

- excellent adhesion to metal and plastic
- for insulating body parts such as the interior, roof and floor sections as well as the bonnet and boot lid and much more.
- absorbs noise and vibrations
- suitable for all frequency ranges
- excellent for CAR HI-FI refurbishment
- dirt-repellent and splash-resistant
- temperature and UV-resistant, resistant to ageing and weatherproof
- against vibrations, anti-buzzing

Areas of application

For eliminating noise sources. For applications in the automotive, vehicle construction, car HiFi and tuning conversion sectors, such as speaker construction, installation of power amplifiers, doorboards, crossovers, soundboards, speaker and speaker construction (woofers, mid-range speakers, tweeters, basses), caravans, buses, shipping, construction and agricultural machinery, heating and mechanical engineering, industry, trades (roller shutter boxes and window sills), as well as for domestic (garage and sink) and DIY applications

TechnicalData

Base	Bitumen
Colours	black
Surface weight	2,02 ± 0,2
Shelf life	36 Months
Temperature Resistance	-40 -+100

Usage Instructions

Application temperature: +5°C to +35°C. Thoroughly clean and degrease the surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Cut body insulation and soundproofing mat to the desired shape using a sharp knife. Then remove the protective film and assemble, pressing evenly and firmly. Full-surface bonding must be ensured. Lower temperatures make processing more difficult. Read the technical data sheet! (Download the PETEC data sheets at www.petec.de)

Package Sizes



Item no.: 87610

500 x 500 x 2 mm