

SCREWLOCK MEDIUM STRENGTH, BLUE

Features

- quick anaerobic curing
- reliably secures fine, medium and coarse threads
- for small and large gap widths and for thread sizes up to M36
- for securing safety-critical screws
- resistant to corrosion, vibration, water, salt water, oil, fuel, coolant and many other chemicals

Areas of application

For securing and sealing threaded connections such as screws, nuts, bolts and much more.

TechnicalData

| | |
|--------------------------|-------------|
| Colours | blue |
| CuringHours | 3-6 |
| Curing system | anaerobic |
| FunctionalStabilityHours | 1 – 3 |
| ThreadSizeUpTo | M36 |
| Hand strength | 10-20 |
| Shelf life | 36 Months |
| Breakaway Torque | 18 – 23 |
| maxGap-fillingCapability | 0,25 |
| Shear strength | 9 – 13 |
| Temperature Resistance | -55 - +200 |
| Viscosity | 2000 - 7500 |

Usage Instructions

Application temperature: +5°C to +35°C. Thoroughly clean and degrease threaded connection with PETEC Multi Cleaner (item no. 82100 or 82200). Attach PETEC screwlock on one side and tighten screws immediately. Tighten the threaded connection to the specified torque. *The anaerobic curing occurs in the absence of air between metallic surfaces. For passive surfaces, large gap widths, low ambient temperature and faster curing, we recommend PETEC anaerobic activator (item. no. 90920). Given the numerous applications, materials and other influencing factors in-house testing and suitability testing is required. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes

| | | |
|--|---|---|
|  |  |  |
| Item no.: 91005 | Item no.: 91010 | Item no.: 91050 |
| 5 g blister pack | 10 g bottle | 50 g bottle |
|  | | |
| Item no.: 910250 | | |
| 250 g bottle | | |