

MULTI-PURPOSE CONTACT ADHESIVE

Features

Strong and immediate adhesion and strong bond.

- multi-purpose
- brush for precise and clean spreading
- also suitable for absorbing material
- weatherproof, UV- and moisture-resistant
- free from aromatic solvents
- resistant to water, salt water, oil, fuel, diluted acids and alkaline solutions

Areas of application

Suitable for bonding small and large pieces of wood, rubber, cork, styrene, felt, rigid PVC, flexible foams, butyl rubber, metal, many plastics, ceramics, leather, linen and many more surfaces (of the same kind or with each other) inside and outside.

TechnicalData

Base	polychloroprene
Colours	clear-yellowish
Flash time	10-15
CuringHours	48
Hand strength	10
Shelf life	24 Months
Shear strength	3
Temperature Resistance	-30 - +120
Consumption	75

Usage Instructions

Application temperature: +5°C to +25°C. Sand back the surfaces if possible, thoroughly clean them and remove any superfluous grease with PETEC Multi Cleaner (item no. 82100 or 82200). Shake well and stir before use. Apply contact adhesive evenly to both surfaces and allow air-drying at room temperature for approx. 10 minutes. Then align the glued surfaces exactly and press them firmly together. Do not tap! Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes



Item no.: 93935

350 ml brush can