

# REPAIR TAPE HIGH PERFORMANCE

## Features

- clear, temperature and pressure resistant
- pressure resistant up to 12 bar
- seals itself, is non-sticky
- clear, extremely strong and tear resistant
- temperature and pressure resistant
- suitable for underwater applications
- shock-resistant
- can even be used on dirty objects
- for indoor and outdoor applications
- weatherproof, UV-resistant and ageing-resistant
- resistant to water, salt water, oil, fuel, coolant and antifreeze

## Areas of application

For sealing, insulating and repairing hoses, cables and pipes. Repairs in the automotive sector (radiator and engine hoses, ignition cables, gaskets and brackets).

## TechnicalData

Colours	clear
Shelf life	36 Months
Dielectric strength	16
Temperature Resistance	-65 - +260
Tensile strength	4,82

## Usage Instructions

Application temperature: +5°C to +40°C. Thoroughly clean and degrease the surface with PETEC Multi Cleaner (item no. 82100 or 82200) if necessary. Cut off the repair tape and remove the clear protective film. Stretch the tape by 1/3 of its length and wrap it tightly around the area to be repaired, allowing an overlap of 30 - 50%. Always conduct your own tests to ensure that the product is suitable for each application. Read the technical data sheet. (Download the PETEC data sheets at [www.petec.de](http://www.petec.de))

### Package Sizes



**Item no.: 94903**

3 m x 25 mm x 0.5 mm