

# TYRE REPAIR SPRAY (CAR)

## Features

- Sealing and inflating at the same time
- for all standard car tyres, regardless of tyre sizes

## Areas of application

PETEC tyre repair spray is suitable for all standard car tyres. Leaks, damaged areas and holes of up to 5 mm in diameter on the tyre surface are repaired within a few minutes. Load bearing capacity is immediately restored and the tyre is ready for use thanks to the rapid repair procedure.

## TechnicalData

Shelf life	36 Months
------------	-----------

## Usage Instructions

Shake the can well before use and remove the plastic safety lock from the spray head. Identify the damaged area and remove any foreign body, if required. Place the valve in the 12 o'clock position (upwards), screw the adapter onto the valve and spray the sealant completely into the tyre. Hold the can upright while doing this. Start driving immediately after application and drive for a distance of 10 km at a maximum speed of 45 km/h! This guarantees an even distribution of the sealant in the tyre. Then check and adjust the air pressure (at the next filling station). Get the tyre replaced immediately and inform the workshop that a repair spray has been used. The integrated tyre pressure monitoring system may be damaged as a result of the application. Read the safety and technical data sheet. (Download the PETEC data sheets at [www.petec.de](http://www.petec.de))

## Package Sizes


<b>Item no.: 70580</b>
400 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.