

CERAMIC PASTE SPRAY

Features

- metal-free, no impairment of sensors in braking systems
- allows easy removal, even after they have been in operation for a long time
- long-lasting resistance to water, salt water as well as to many acids and alkaline solutions
- metal-free lubrication, anticorrosive
- silicone-free
- 360°-valve, can be used upside down

Areas of application

For long-term lubrication of highly-stressed sliding surfaces of all types as well as for bayonet, plug-in and screwed joints exposed to high temperatures and corrosive influences such as braking systems, pipe, flange and valve screws.

TechnicalData

Colours	white
Shelf life	36 Months
Temperature Resistance	-20 - +1500

Usage Instructions

Shake can well before use. Remove excess material with a wire brush and then thoroughly clean and degrease with PETEC brake cleaner (item no. 70060). Spray an even coat of PETEC ceramic paste spray on the thread in question or on the surfaces. Then assemble the parts as required. Note: Do not apply to the brake disc or the friction side of the brake pad. Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes


Item no.: 70650
500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.