TechDataSheet

LEAK DETECTION SPRAY

Features

- · a leak is indicated by strong bubble or foam formation
- simple and reliable

- for leak detection
- non-flammable
- ecofriendly
- silicone-free
- non-corrosive
- skin-compatible
- DVGW (German Technical and Scientific Association for Gas and Water) approval
- 360°-valve, can be used upside down

Areas of application

For quick and effortless detection of leakages in pipelines under pressure, on fittings, flange connections, welded seams and tyres.

TechnicalData

Colours	clear
Shelf life	36 Months

Usage Instructions

Shake can well before use. Apply PETEC leak detection spray to any suspicious area. A leak will be indicated by excess foaming or bubbling at the defective area (leak). Plastic pipelines and coated surfaces must be cleaned with clean water after testing. Do not use for testing oxygen-pipelines! Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes

PERSEC LECKSUC SPRAY WITH WITH WITH WITH WITH WITH WITH WITH	
Item no.: 70750	
400 ml	

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.

www.petec.de