

WELDING & PROTECTIVE SEPARATOR SPRAY

Features

- protects parts and nozzles
- no mechanical removal of welding spatter necessary
- 100% protection whilst welding
- no impairment on the weld joint
- extends the service life of welding nozzles
- suitable for many surfaces
- non-flammable
- silicone-free

Areas of application

PETEC welding & protective separator spray forms a protective film, which prevents the adhesion of welding spatter or welding beads on surfaces.

TechnicalData

Shelf life	36 Months
------------	-----------

Usage Instructions

Shake can well before use. Thoroughly clean the area to be treated with PETEC brake cleaner. Apply PETEC welding and protective separator spray evenly on a wide area of the surface to be protected from a distance of approx. 20 cm. Clean the area again after welding. Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes



Item no.: 72050

500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.