

OIL BINDER

Features

- easy to use
- quick and economic
- suitable as a chemical binder type B, F, H, P
- can be used for small and large areas indoors and outdoors
- environmentally sound, 100% recycled product
- can also be used on wet substrates
- suitable as a chemical binder (pre-test) - Avoid contact with strong acids and oxidising agents
- Type: Type III R fine – 40 litres
- grain size: 0.125 mm – 1 mm
- oil binding: 1 litre PETEC oil binder binds 0.86 l oil

Areas of application

For binding of polluting fuel and oil spills on absorbent and non-absorbent surfaces such as concrete, asphalt, plaster, tiles and many more. For automotive and truck repair shops, fire stations, motorway and road maintenance depots, petrol stations, industrial and craft businesses, hauliers, vehicle recovery services and in agriculture.

TechnicalData

Shelf life	Months
------------	--------

Usage Instructions

Apply a 5 cm thick layer of oil binder to the oiled surface and let it act. If necessary, move the binder with a broom back and forth to obtain a better result. Then remove the oil binder. Read the technical data sheet. (Download the PETEC data sheets from www.petec.de)

Package Sizes



Item no.: 72320

40 litres/20 kg sack

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.