

TechDataSheet

OIL STAIN REMOVER SPRAY

Features

- binds and removes oil spills
- easy to use
- quick and economic
- · removes persistent oil stains
- · excellent suction power
- silicone-free

Areas of application

For binding and removing environmentally harmful fuel and oil spills on absorbent and non-absorbent surfaces. Excellent on many materials (concrete, asphalt, plaster, tiles) in/on e.g. workshops, petrol stations, driveways, streets and much more

TechnicalData

Shelf life 36 Months

Usage Instructions

Shake can well before use. Apply PETEC oil stain remover to the oiled surface from a distance of approx. 20 cm and let it act for 20–30 minutes. After the drying time, remove residues and repeat the process if necessary. Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Warning: The spray removes moisture from the substrate, which can temporarily lead to white staining. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes



Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.