

STONE CHIP & UNDERBODY PROTECTION BLACK

Features

- protects repair and body parts from rust and stone chips
- very good adhesion to many surfaces
- forms an elastic, structural and unified protective film with anti-buzzing effect.
- can be re-coated
- does not become brittle or cracked and adheres even at high temperatures
- breathable underbody protection, also suitable for wood applications in the caravan sector
- no streak formation and does not drip
- resistant to water, salt spray, oil as well as diluted acids and bases

Areas of application

PETEC synthetic rubber-based stone chip and underbody protection can be re-coated and adheres very well to many surfaces. For optimum protection against rust and stone chips in many corrosion-prone areas. After drying, stone chip and underbody protection forms an elastic, structural and unified protective film with anti-buzzing effect.

TechnicalData

Base	synthetic rubber
Colours	black
Curing	2 hours at 500 µm
Curing system	Humidity
Shelf life	36 Months
Salt spray test	480 at 350 µm (Ri0)
Temperature Resistance	-30 - + 100

Usage Instructions

Application temperature: +5°C to +30°C. Shake well before use. Spray PETEC stone chip and underbody protection on the rust-free, clean, dry and degreased surface from a distance of approx. 25 cm. Can be re-coated after the drying time*. Varnishes and other media containing solvents may inhibit or ruin the curing process. For thicker layers, we recommend to let the product dry, before applying the next layer. Check on beforehand if the materials are compatible. Danger of autoxidation on alloys. The product contains solvents which may dissolve or attack existing coatings. Different underbody protection products should therefore not be combined with each other without conducting your own tests first. Always conduct your own tests to ensure that the product is suitable for each application. Do not apply on the brake and exhaust system, heat plates or rubber parts. After use, turn the can upside down and spray until the valve is empty. Read the safety and technical data sheet! (Download the PETEC data sheets at www.petec.de)

TechDataSheet

Package Sizes

	
Item no.: 73210	Item no.: 73250
1000 ml	500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.