

TechDataSheet

MULTI UNDERBODY PROTECTION WAX TRANSLUCENT VACUUM CAN

Features

- · protects and maintains body and metal parts
- fast-drying duroplastic protective film
- very good adhesion
- heat-resistant up to +200°C
- moisture displacing
- · extremely well suited for protection and post-conservation
- · flexible and slightly tacky wax layer with excellent temperature resistance
- will not crack or become brittle
- outstanding ability to penetrate
- · very good heat resistance and good flexibility when cold
- · resistant to water, salt spray, oil as well as diluted acids and bases

Areas of application

PETEC Multi underbody protection wax offers ideal anti-corrosion and anti-stone chip protection properties in corrosionprone areas and bonds to many surfaces. Thanks to its outstanding ability to penetrate, Multi underbody protection wax can also reach hard-to-reach cavities in the vehicle body.

TechnicalData

Base	paraffin wax
Base	Oil
Colours	Translucent
Working pressure	3 - 4
Curing	2 hours at 500 μm
Shelf life	36 Months
Salt spray test	1,000 at 100 μm (Ri0)
Temperature Resistance	-35 - +200

Usage Instructions

Application temperature: +5°C to +30°C. Shake well before use. Spray PETEC Multi underbody protection wax on the rustfree, clean, dry and degreased surface from a distance of approx. 25 cm using the PETEC underbody protection gun (item no. 98507) and screw on the hose if necessary. For thicker layers, we recommend to let the product dry, before applying the next layer. Check on beforehand if the materials are compatible. Danger of autoxidation on alloys. The product contains solvents which may dissolve or attack existing coatings. Different underbody protection products should therefore not be combined with each other without conducting your own tests first. Always conduct your own tests to ensure that the product is suitable for each application. Cannot be re-coated.

Do not apply on the brake and exhaust system, heat plates or rubber parts. Clean the underbody protection gun after use. Read the safety and technical data sheet! (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.

www.petec.de



TechDataSheet

Package Sizes

Item no.: 73410	ltem no.: 73450
1000 ml	500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.

www.petec.de