

TechDataSheet

MULTI UNDERBODY PROTECTION WAX BLACK VACUUM CAN

Features

- protects and maintains body and metal parts
- · fast-drying, long-lasting duroplastic protective film
- very good adhesion
- heat-resistant up to +200°C
- · displaces moisture
- extremely well suited for protection and post-conservation
- flexible and slightly adhesive wax layer with excellent temperature resistance
- will not crack or become brittle
- · outstanding ability to penetrate
- high heat resistance and good flexibility at low temperature
- resistant to water, salt spray, oil as well as diluted acids and bases

Areas of application

PETEC Multi underbody protection wax offers ideal protection against corrosion and stone chips in corrosion-prone areas and bonds to many surfaces. Thanks to its outstanding penetration capability, Multi underbody protection wax can also reach hard-to-reach body cavities.

TechnicalData

Base	paraffin wax
Base	Oil
Colours	black
Working pressure	3 - 6
Curing	2 hours at 500 μm
Shelf life	36 Months
Salt spray test	1,000 at 100 µm (Ri0)
Temperature Resistance	-35 - +200

Usage Instructions

Application temperature: +5°C to +30°C. Shake can well before use. Spray PETEC Multi underbody protection wax on the rust-free, clean, dry and degreased surface from a distance of approx. 25 cm using the PETEC underbody protection gun (item no. 98507) and screw on the hose if necessary. For thicker layers, we recommend to let the product dry before applying the next layer. Check on beforehand if compatible with the material. Danger of autoxidation in alloys. The product contains solvents which may dissolve or damage existing coatings. Different underbody protection products should therefore not be combined with each other without conducting your own tests on beforehand. Always conduct your own tests to ensure that the product is suitable for each application. Re-coating is not possible. Do not apply to the brake and exhaust system, heat plate or rubber parts. Clean the underbody protection gun after use. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.



TechDataSheet

Package Sizes

PETEC MULTI UBS WAX Complete SCHWAR Tables on define change I show the definition c	PETEC MUST USS SCHWAR SCHWAR
Item no.: 73420	Item no.: 73460
1000 ml	500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.