

TechDataSheet

ENGINE PROTECTION WAX SPRAY

Features

- glossy anti-corrosive
- protects and maintains plastic and metal parts
- displaces moisture
- extremely well suited for protection and post-conservation
- resistant to ageing and weathering

Areas of application

PETEC engine protection wax & preservation is a glossy sealant and anti-corrosive. Protects, maintains and seals the engine compartment and many other parts. Provides reliable protection against corrosion, dirt, moisture and leakage currents.

TechnicalData

Colours	Translucent
Shelf life	36 Months
Temperature Resistance	-30 - +100

Usage Instructions

Shake can well before use. Spray PETEC engine protection wax on the rust-free, clean, dry and degreased surface from a distance of approx. 25 cm. Check on beforehand if compatible with the material. Danger of autoxidation in alloys. The product contains solvents which may dissolve or damage existing coatings. Always conduct your own tests to ensure that the product is suitable for each application. Re-coating is not possible. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes



Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.