

# BODY CAVITY PROTECTION & CONSERVATION TRANSLUCENT

## Features

- Long-term corrosion protection for body cavities
- fast-drying duroplastic protective film
- moisture displacing, does not form cracks or become brittle
- flexible and slightly sticky wax layer
- very good ability to penetrate, barely-accessible body cavities can also be reached
- infiltrates and displaces moisture
- very good heat resistance and good flexibility when cold
- resistant to water, salt spray, oil as well as diluted acids and bases
- comes with 60 cm spray probe (spray)

## Areas of application

Offers optimum protection in all corrosion-prone areas. Thanks to its outstanding ability to penetrate, barely accessible body cavities can also be reached.

## TechnicalData

Base	paraffin wax
Colours	Translucent
Shelf life	36 Months
Salt spray test	1,000 at 100 µm (Ri 0)
Temperature Resistance	-35 - +200

## Usage Instructions

Application temperature: +5°C to +30°C. Shake well before use. Spray PETEC body cavity protection & conservation on the rust-free, clean, dry and degreased surface. For thicker layers, we recommend to let the product dry, before applying the next layer. Applying multiple coatings may cause white colouration of the wax. Check on beforehand if the materials are compatible. Danger of autoxidation on alloys. The product contains solvents which may dissolve or attack existing coatings. Different underbody protection products should therefore not be combined with each other without conducting your own tests first.

Always conduct your own tests to ensure that the product is suitable for each application. Cannot be re-coated. Do not apply on the brake and exhaust system, heat plates or rubber parts. After use, turn the can upside down and spray until the valve is empty. Read the safety and technical data sheet. (Download the PETEC data sheets at [www.petec.de](http://www.petec.de))

### Package Sizes

	
<b>Item no.: 73510</b>	<b>Item no.: 73550</b>
1000 ml	500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.