

TechDataSheet

ENGINE OIL SYSTEM CLEANER

Features

- cleans
- dissolves
- protects
- maintains
- for cleaning petrol and diesel engines as well as manual gearboxes, differentials and other units before every oil change
- compatible with all rubber, metal and plastic parts, does not corrode engine seals.
- · suitable for all engines and compatible with all engine oils

Areas of application

Premium additive for cleaning the engine oil circuits of all engine types. PETEC engine oil system cleaner is an engine cleaner suitable for all oil circuits in petrol and diesel engines in cars, trucks, boats, tractors and much more. The highly effective cleaning concentrate dissolves dirt and sludge deposits throughout the complete oil circuit.

TechnicalData

Colours	yellowish, medium viscosity oil
Shelf life	36 Months
Consumption	3% of the total oil volume

Usage Instructions

Shake well before use. 300 ml of cleaner is sufficient for approx. 5 litres of oil. The amount of cleaner must be adjusted to the total amount of oil in the system, which depends on the vehicle. Ensure that the oil amount does not fall below the minimum oil level. Remove the cap of the cleaner and pour the contents into the warm engine (via the engine oil filler spout). Let the engine run in neutral for approx. 10 minutes. Then change the filter and oil immediately and fill the oil system according to the manufacturer's instructions. Not suitable for slip clutches. Follow the vehicle manufacturer's instructions and read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.



TechDataSheet

Package Sizes



300 ml can

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.