

CLEANING CLOTH

Features

- for removing silicone residue from the bonding surface of windscreens
- residue free

Areas of application

For cleaning and degreasing bonding surfaces before using adhesives and sealants.

TechnicalData

Base	99.9 % IPA isopropanol
Colours	clear
Flash time	10
Shelf life	24 Months
Application temperature	+5 - +35

Usage Instructions

Application temperature: +5°C to +35°C. Commercially available cleaning agents and glass cleaners are not suitable for pre-treatment in case of window adhesion. Lightly sand the bonding surface with the supplied abrasive fleece, and then thoroughly clean and degrease in one direction with the PETEC cleaning cloth. Depending on the amount of contamination, it may be necessary to repeat the process. All dirt, dust, oil, fat and wax must be removed from the bonding surface without leaving any residue. Also ensure that the surface to be treated is free from any silicone contamination. After air drying for approx. 10 minutes, the adhesive surface can be further processed (e.g. primer and activator or direct adhesive application). Follow the installation instructions and read the safety and technical data sheet. (Download PETEC installation instructions, data sheets and application videos at www.petec.de)

Package Sizes



Item no.: 82111

1 piece

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.