

BLACK PRIMER

Features

- excellent coverage (colour: black)
- adhesion promoter and UV protection of PU-based adhesives and sealants
- also for touching up damage on the body flange

Areas of application

Adhesion promoter and UV protection for pre-treatment of the bonding surface for windows with and without ceramic screen printing coating

TechnicalData

Base	Mixture
Colours	black
Flash time	10
Shelf life	12 Months
Application temperature	+5 - +35

Usage Instructions

Thoroughly clean and degrease the bonding surface of the window with PETEC cleaning cloth (item. no. 82111). Follow the air drying time. Shake bottle well before use. Apply black primer with wool wiper (item no. 82222) evenly in one direction on the bonding surface of the window and over a slightly wider area where the glue bead overlaps. Do not start to apply the adhesive until the air-drying time has been reached. To prevent corrosion, minor paint damage on the body flange is repaired with PETEC black primer. Follow the air drying time. If the body flange is painted, the area must be cleaned again after complete curing of the paint and primed with black primer. Carefully read the installation instructions and safety data sheet (Download PETEC installation instructions, data sheets and application videos at www.petec.de)

Package Sizes

Item no.: 82330
30 ml can

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.