

# PRIMER AND ACTIVATOR STICK

## Features

### Adhesion promoter

- for adhesion on windows with and without a ceramic screen printing coating with excellent UV protection

### Activator

- for activating PU-RIM and PVC coatings
- easy to apply using a screw-on applicator
- excellent coverage (colour: black)
- adhesion promoter and UV protection of PU-based adhesives and sealants

## Areas of application

Combines the advantages of black primer and activator in one product.


## TechnicalData

Base	Mixture
Colours	black
Flash time	10
Shelf life	12 Months
Application temperature	+5 - +35

## Usage Instructions

Application temperature: +5°C to +35°C. **IMPORTANT:** Commercially available cleaning agents and glass cleaners are not suitable for pre-treatment in case of window adhesion. Lightly sand the bonding surface with the supplied abrasive fleece and then thoroughly clean and degrease with the PETEC cleaning cloth (item no. 82111) or PETEC MULTI Cleaner (item no. 82100). All dirt, dust, oil, fat and wax must be removed from the bonding surface without leaving any residues. Also ensure that the surface to be treated is free from any silicone contamination. Stubborn silicone contamination must be removed using our sealant and adhesive remover spray (item no. 82150). Shake the primer and activator stick thoroughly before use. Open the tube membrane with the felt applicator and screw on completely. Apply primer and activator evenly in one direction on the bonding surface and over a slightly wider area where the glue bead overlaps. Do not start to apply the adhesive until the air-drying time\* has been reached. Shake primer and activator until the contents have been uniformly mixed and can be applied in deep black. Apply several coats of primer and activator if required. Follow the installation instructions, application video and read the safety and technical data sheets. (Download the PETEC data sheets at [www.petec.de](http://www.petec.de))

### Package Sizes


<b>Item no.: 82410</b>
10 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.