

# FOAM ASSEMBLY TAPE, BLACK

## Features

Double-sided foam tape with good adhesion strength for cars, handwork, industry, exhibition stand and stage construction, and more.

- for numerous material combinations
- high-strength adhesion
- excellent shear strength
- reduces vibration
- bridges gaps
- can replace screws and rivets
- for indoor and outdoor applications
- very good UV-resistance

## Areas of application

Good adhesion to many materials such as metal, glass, stone, tiles, wood and different plastics. For fastening trim strips, emblems, equipment and more. Assembly of brackets, mirrors, pictures, signs, attached parts, hooks and much more.

## TechnicalData

Colours	black
Shelf life	36 Months
Shear force	6
Temperature Resistance	-40 - +120
Tensile strength	19,6 N /25 mm

## Usage Instructions

Application temperature +5°C to +35°C. Thoroughly clean and degrease surface with PETEC Multi Cleaner (item no. 82100 or 82200). Stick the assembly tape to one of the surfaces to be bonded. Then remove the green protective foil and bond to the intended area, pressing firmly. In-house testing and suitability testing is required given the numerous applications, materials and other influencing factors.

Read the technical data sheet. (Download the PETEC data sheets at [www.petec.de](http://www.petec.de))

&nbsp;

### Package Sizes

<p>The image shows a circular roll of PETEC TAPE line SCHAUMSTOFF MONTAGEBAND. The label is green and white with black text. It features the PETEC logo at the top, followed by 'TAPE line' and 'SCHAUMSTOFF MONTAGEBAND'. Below this, it lists applications: 'Für viele Materialkombinationen', 'Für Innen- und Außenverklebung', 'Hochwertiges Klebeband mit hoher Klebekraft', 'Vibrationsdämmend', and 'Spaltfüllband'. There are also handwritten notes in red: 'doppelseitig' and 'Nebend'. At the bottom, it says 'VERBODEN TOEGEVOEGD BIJ ANDERE KLEBEKSTOFFEN'.</p>	<p>The image shows a rectangular roll of PETEC TAPE line SCHAUMSTOFF MONTAGEBAND. The label is green and white with black text. It features the PETEC logo at the top, followed by 'TAPE line' and 'SCHAUMSTOFF MONTAGEBAND'. Below this, it lists applications: 'Für viele Materialkombinationen', 'Für Innen- und Außenverklebung', 'Hochwertiges Klebeband mit hoher Klebekraft', 'Vibrationsdämmend', and 'Spaltfüllband'. At the bottom, it says 'VERBODEN TOEGEVOEGD BIJ ANDERE KLEBEKSTOFFEN'.</p>
<p><b>Item no.: 87200</b></p>	<p><b>Item no.: 87122</b></p>
<p>10mx19mmx1mm</p>	<p>2 m x 12 mm x 1 mm</p>

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.