

BODY, CONSTRUCTION AND JOINT SEALING TAPE

Features

For sealing joints and overlaps against driving rain, wind, noise, dust and spray water.

- one-sided adhesive and foaming sealing tape
- it moulds itself to seal the gap
- non-destructive removal
- very good sound and heat insulation properties
- immediate further processing
- categorised in accordance with BG1 (resistant to external weather effects) and BGR (airtight); B1 (flame resistant)

Areas of application

For sealing joints and expansion joints in the area connecting the walls and ceiling between concrete components, skylight surrounds, window frames, masonry and windowsill connections in the construction of trapezoidal sheet metal, sandwich construction, metal construction, solid construction, wood construction, and drywall construction. For joints and overlaps in the bodywork e.g. mudguards, sliding roofs, brake lights and reversing lights, number plates and other body parts.

TechnicalData

Colours	black
Joint sound insulation	59
Shelf life	36 Months
Water tightness	600
Temperature Resistance	-30 - +90

Usage Instructions

Application temperature +5°C to +35°C. Thoroughly clean and degrease surface with PETEC Multi Cleaner (item no. 82100 or 82200). Cut the tape to the desired length and peel off the white protective film. Then glue onto one of the two surfaces and carry out assembly/screwing. Always conduct your own tests to ensure that the product is suitable for each application. Read the technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes


Item no.: 87430
5.6 m x 15 mm x 5-12 mm

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.