

ACTIVATOR ANAEROBIC SPRAY

Features

Curing accelerator for anaerobic adhesive and sealants. Especially recommended for:

- passive surfaces
- large gaps
- as well as at low temperatures

Areas of application

Significantly shortens the hardening time of anaerobic PETEC products, such as screw locking, pipe and thread seals, hydraulic and pneumatic seals, bearing fix and surface seals. Recommended particularly for passive surfaces, such as aluminium, magnesium and stainless steel, large gaps and low temperatures.

TechnicalData

Colours	clear
Flash time	2
Shelf life	36 Months

Usage Instructions

Application temperature: -30°C to $+35^{\circ}\text{C}$. Remove old sealants and deposits. Thoroughly clean and degrease surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Shake can well before use. Spray the activator for anaerobic adhesives & spray sealants evenly on one of the two surfaces from a distance of approx. 20 cm and allow to dry for approx. 2 minutes. Apply the anaerobic product/adhesive to the opposite surface and assemble immediately. Check on beforehand if compatible with the material. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes


Item no.: 90920
200 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.