

SPEEDBOND HIGH-PERFORMANCE ADHESIVE

Features

For super quick bonding of various materials, e.g. plastic and plastic compounds, metal, rubber, ceramic, porcelain, wood and many others.

Areas of application

SpeedBond Set for the structural bonding and repairing of broken parts. Bonding and repair of plastic, metal, rubber, ceramics, porcelain, wood and much more. Even the smallest holders and clips can be repaired.

TechnicalData

Base	ethyl cyanoacrylate
Colours	clear
Functional stability	3-10
Shelf life	18 Months
Gap Bridging	0.05
Temperature Resistance	-40 - +85
Tensile Shear Strength	15-25

Usage Instructions

Application temperature: +5°C to +30°C. Clean parts to be bonded thoroughly and remove any grease with PETEC Multi Cleaner (item no. 82100 or 82200). For quicker hardening, we recommend SpeedBond Activator spray (item no. 93515). Apply a thin layer of SpeedBond high-performance adhesive on one side and unite the parts immediately. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes


Item no.: 93520
20 g bottle

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.