

TechDataSheet

MULTI-FUNCTIONAL SEAM SEALANT GREY

Features

For sealing body parts and overlapping connecting joints.

- broad range of adhesive applications
- · permanent joints
- permanently elastic and excellent sealing properties
- can be coated immediately (wet-on-wet)
- silicone-free and isocyanate-free
- solvent-free (material does not shrink after through-drying)
- · resistant to ageing, weatherproof and UV-resistent

Areas of application

1 component sprayable and spreadable seam sealant for sealing weld seams, overlaps and for restoring the original structure after an accident repair, e.g. in the engine compartment area, boot, underbody, wheel arches and on all overlapping assembly seams.

TechnicalData

Base	MS polymer
Colours	grey
Curing	3
Curing system	Humidity
Shelf life	24 Months
Elongation at break	150
ShoreAHardness	40
Temperature Resistance	-40 - +100
Pot life	15
Tear propagation resistance	8
Tensile strength	2

Usage Instructions

Application temperature: +5°C to +40°C. Thoroughly clean and degrease surface with PETEC Multi Cleaner (item no. 82100 or 82200). Cut open the cartridge above the thread and screw on the nozzle. Apply the seam sealant using an applicator gun or the telescopic compressed air gun, Multipress (item. no. 94333). To restore the original structure, you can adjust the material feed, air supply and distance. Can be immediately coated (wet-on-wet) with water-based paint. Varnishes and other media containing solvents may inhibit or ruin the curing process. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.



TechDataSheet

Package Sizes

PEULEC CHARACTURE AND THE CONTROL OF	PETIEC WITH THE MENT AND THE M
Item no.: 94131	Item no.: 94231
310 ml	310 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.