

TechDataSheet

SPRAY ADHESIVE

Features

- multi-purpose, even for styrene and absorbent materials
- weatherproof, UV- and moisture-resistant
- clean and easy to use
- clear bonding, the adhesive does not penetrate through the material
- · resistant to water and salt water

Areas of application

PETEC spray adhesive with high immediate adhesive strength for large-area bonds indoors and outdoors as well as absorbent and non-absorbent materials. Bonds materials such as leather, foam, rubber, textiles, felt, styrene, wood, cork, cardboard, paper, insulating boards, plastic, metal and much more. PETEC spray adhesive is ideal for automotive applications (roof liner, parcel shelf, upholstery, insulating mats and foils and much more), caravans, boats, industry, trade, model-making, household, etc.

TechnicalData

Base	polychloroprene
Colours	clear
Flash time	3
CuringHours	12
Hand strength	2
Shelf life	24 Months
Shear strength	3
Temperature Resistance	-30 - +80
Consumption	75

Usage Instructions

Application temperature: +5°C to +25°C. Shake can well before use. Thoroughly clean and degrease the surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Apply the spray adhesive evenly from approx. 25 cm to both surfaces and allow air-drying at room temperature for approx. 3 minutes (depending on coat thickness). Once the fixing point has been reached, line up the surfaces exactly and press, roll or push them firmly together. Do not tap! The parts to be bonded will adhere immediately. After use, turn the can upside down and spray until the valve is empty. Check on beforehand if compatible with the material. Always conduct your own tests to ensure that the product is suitable for each application. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.



TechDataSheet

Package Sizes



400 ml spray

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.