

# BRAKE SERVICE PASTE

## Features

- prevents braking and squeaking noise
- very low oil separation and thus extremely long lasting
- very economical with high washout resistance; does not wash out with splashing water and does not dry out with fluctuating temperatures
- metal-free lubricant, no impairment of sensors in braking systems
- acid-free, non-conductive and non-corrosive and therefore compatible with all types of metals and rubbers
- resistant to cold and high temperatures as well as splashing and salt water

## Areas of application

Lubricating, sliding, release and corrosion protection agent for long-term lubrication of highly stressed sliding surfaces and joints of all kinds. Also as an assembly aid on machines and to prevent run-in damage and wear on bearings, sliding points, screwed and plug-in connections.

## TechnicalData

Colours	clear-yellowish
Shelf life	60 Months
Temperature Resistance	-30 - +120

## Usage Instructions

Remove excess material with a wire brush and then thoroughly clean and degrease with PETEC brake cleaner (item no. 70060). Apply an even coat of PETEC Slide-Lube on the stressed threads and surfaces. Then assemble the parts as required. Note: Do not apply to the brake disc or the friction side of the brake pad. Given the numerous applications, materials and other influencing factors in-house testing and suitability testing is required. Read the safety and technical data sheet! (Download the PETEC data sheets from [www.petec.de](http://www.petec.de))

## Package Sizes

 <p>The image shows a sachet of PETEC Brake Service Paste. The sachet is white with a green and black design. The text on the sachet includes 'PETEC BREMSEN SERVICEPASTE anti-squeak' and translations in multiple languages: 'BRAKE PASTE (ANTI-SQUEAK)', 'PASTE POUR SERVICE FREINS', 'PASTA PROTETTIVA PER FRENO', 'BREMSENSERVICEPASTE', 'SERVISNI PASTA NA BRZDY', 'HÁZTÁRTIA SZÉPÍTÉS ÖRSENY', and 'FRENS SERVICE MASCIUO'. It also lists the manufacturer: 'PETEC Verbindungstechnik GmbH, www.petec.de, Wüstenbuch 26   D-96132 Schlüsselfeld   Tel.: +49 95 55-80 99 40'.</p>
<b>Item no.: 94405</b>
5 g sachet

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.