

REPAIR TAPE

Features

Self-sealing repair tape is easy to manage and apply.

- seals itself, is non-sticky
- pressure-resistant
- shock and tear-resistant
- excellent resistance to water, temperature and UV
- can even be used on dirty objects
- resistant to water, salt water, coolants, antifreeze, etc.

Areas of application

For sealing, insulating and repairing hoses, cables and pipes. Repairs in the automotive sector (radiator and engine hoses, ignition cables, gaskets and brackets).

TechnicalData

Colours	black
Shelf life	36 Months
Dielectric strength	42
Temperature Resistance	-40 - +90
Tensile strength	2

Usage Instructions

Application temperature: +5°C to +40°C. Thoroughly clean and degrease the surface with PETEC Multi Cleaner (item no. 82100 or 82200) if necessary. Cut off the repair tape and remove the white protective film. Stretch the tape by 1/3 of its length and wrap it tightly around the area to be repaired, allowing an overlap of 30 - 50%. Always conduct your own tests to ensure that the product is suitable for each application. Read the technical data sheet. (Download the PETEC data sheets at www.petec.de)

Package Sizes


Item no.: 94905
5 m x 19 mm x 0.5 mm

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.