

TechDataSheet

SURFACE SEAL, ORANGE, MEDIUM STRENGTH

Features

Hardening seal for sealing metal surfaces and flanged joints, for example in pumps, gearbox housings, differentials and motor flanges.

- · quick anaerobic curing
- replaces solid seals, levels surface roughness
- no compression set of the seal and no loss of clamping force
- resistant to corrosion, vibration, load, heat, water, salt water, oil, fuel, coolant, hydrocarbon and many other chemicals

Areas of application

Automotive, engine, gear, machine construction (pumps, gearbox housing, differentials and motor flanges).

TechnicalData

Colours	orange
Curing system	anaerobic
FunctionalStabilityHours	3 - 6
Hand strength	15-30
Shelf life	36 Months
Gap Bridging	0.5
Temperature Resistance	-55 - +150
Viscosity	30 - 100
Tensile Shear Strength	5–10

Usage Instructions

Application temperature: +5°C to +35°C. Remove old sealants and excess material, thoroughly clean and degrease sealing surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Apply the desired coat thickness on one side (also in bores or on threads), then join the parts to be sealed together. Tighten the threaded connection to the specified torque. *The anaerobic curing occurs in the absence of air between metallic surfaces. For passive surfaces, large gap widths, low ambient temperature and faster curing, we recommend PETEC anaerobic activator (item. no. 90920). Given the numerous applications, materials and other influencing factors in-house testing and suitability testing is required. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.



TechDataSheet

Package Sizes

FLACHEN DICKTUNG WAR AND THE STATE OF THE S	FEGURE DE LE CONTROL DE LE CON
Item no.: 971250	Item no.: 97175
250 ml tube	75 ml press box

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.