

# UNIPLAST SEAL

## Features

Filler for solid gasket seals

- enhances solid gasket seals (e.g. cork, paper, rubber, metal) and improves sealing properties on a long term basis.
- remains malleable, does not harden
- immediate further application possible
- silicone-free and solvent-free
- resistant to water, salt water, oil, fuel, coolant, antifreeze and many other chemicals

## Areas of application

Housing, pump, surface and flange connections in combination with solid seals.


## TechnicalData

Colours	blue
Curing system	malleable
Functional stability	immediately
Shelf life	36 Months
Temperature Resistance	-50 - +180
Viscosity	1.200.000

## Usage Instructions

Application temperature: +5°C to +35°C. Thoroughly clean and degrease sealing surfaces with PETEC Multi Cleaner (item no. 82100 or 82200). Apply sealing compound and fit immediately. Given the numerous applications, materials and other influencing factors in-house testing and suitability testing is required. Read the safety and technical data sheet! (Download the PETEC data sheets from [www.petec.de](http://www.petec.de))

## Package Sizes


<b>Item no.: 97510</b>
80 ml tube blister pack

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.