TechDataSheet

PLASTIC PRIMER SPRAY

Features

short flash time

- colourless
- · improved adhesion especially for plastics that are difficult to glue

Areas of application

Adhesive agent for improving the bonding of 1-component and 2-component adhesives on plastics. PETEC plastic primer improves the adhesion of adhesives, especially with low-energy or difficult-to-bond plastics, such as PE, PP, PU, PC, PA, EPDM, POM, Teflon, PTFE, PVC, Plexiglas, GRP and many more.

TechnicalData

Colours	clear
Flash time	5-10
Shelf life	36 Months
Application temperature	+5 - +30

Usage Instructions

Application temperature: +5°C to +30°C. Clean surfaces thoroughly and degrease well with PETEC Multi Cleaner (item no. 82100 or 82200). Shake can well before use. Apply an even coat of plastic primer from a distance of approx. 25 cm on the surface to be bond. Once the flash time* has passed, you can continue with glueing. Check on beforehand if compatible with the material. Read the safety and technical data sheet! (Download the PETEC data sheets from www.petec.de)

Package Sizes



Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.