

# RUST DISSOLVER SPRAY MOS2

## Features

- dissolves rust quickly
- good penetration capabilities, penetrates into rust
- displaces moisture
- protects against corrosion
- good lubrication properties, eliminates squeaking noises
- silicone-free
- 360° -valve, can be used upside down

## Areas of application

For quick loosening of tight connections such as screws, nuts and bolts. Due to its strong capillary effect and very good penetration capabilities the rust dissolver enters even into the smallest gaps. By applying MoS<sub>2</sub>, the PETEC rust dissolver can also be used in extreme temperatures and with high pressure loads. Rust dissolver – for rusted screw and metal connections Lubricant – for moving parts, removes squeaking noises Preservative – long-term removing of flash rust and preservation Corrosion protection and maintenance agent – provides long-term protection against corrosion

## TechnicalData

Shelf life	36 Months
------------	-----------

## Usage Instructions

Shake can well before use. Remove excess material with a wire brush. Spray PETEC rust dissolver MoS<sub>2</sub> onto the entire surface of the seized parts and loosen the fitting after a few minutes. Check on beforehand if compatible with the material. Read the safety and technical data sheet! (Download the PETEC data sheets from [www.petec.de](http://www.petec.de))

## Package Sizes


<b>Item no.: 70050</b>
500 ml

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.