PETEC

TechDataSheet

INJECTOR SOLVENT SPRAY

Features

- rapid disassembly
- intensive effect
- outstanding ability to penetrate
- fast dissolving, infiltrates rust/deposits
- silicone-free
- 360°-valve, can be used upside down

Areas of application

Innovative special rust dissolver effective even in the smallest pores thanks to its remarkable deep action. Due to the good penetration capability, rust and deposits are infiltrated. Quickly and gently loosens seized connections on attached parts (such as injectors, glow and spark plugs, spray nozzles, exhaust, manifold, lambda probes, tie rods and many more).

TechnicalData

Colours	clear
Shelf life	36 Months

Usage Instructions

Shake can well before use. Remove coarse deposits with a wire brush, if possible. Spray the PETEC injector Solvent onto the entire surface of the seized parts and loosen the fitting after waiting a few minutes. The longer the contact time, the lower the breakaway torque. Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)

Our technical application advice, whether verbal, in writing, or based on tests, is provided to the best of our current knowledge. However, it does not release you from the obligation to independently verify the suitability of the products we supply for the intended processes and purposes. The application, use, and processing of the products are beyond our control and therefore fall solely within your area of responsibility.

PETEC Verbindungstechnik GmbH | Wüstenbuch 26 | D-96132 Schlüsselfeld | Tel.: +49 95 55-80 99 40 | Fax: +49 95 55-80 99 425 | info@petec.de