

PRIMER FILLER

Features

- High-build filling properties and corrosion protection
- Fast-drying
- Ready-to-use - no mixing required
- Excellent sanding properties
- Chromate-free
- Fine spray dispersion for smooth transitions
- Can be re-coated with 1C and 2C topcoat systems (solvent & water based)
- Compatible with PETEC Epoxy Primer (Art. No. 71140), PETEC Body Solder (Art. No. 96175), PETEC Clear Coat (Art. No. 71340), and PETEC Body Fillers (Art. Nos. 96125, 96110, 96225, 96210, 96325, and 96310)

Areas of application

1-component Primer Filler is a reliable and user-friendly repair filler designed for fast and efficient repair work. It provides excellent adhesion to steel, aluminium, galvanized substrates and sanded, sound existing paint finishes. Its fine atomization ensures smooth, even coverage across surfaces and run-off zones, while providing effective protection against moisture. Its fast drying time and easy application, means this coating is ideal for everyday use in both professional workshops and DIY applications.

TechnicalData

Base	epoxy resin
Colours	grey
Touch dry	10
Shelf life	36 Months
Dry dust-free	5
Drying Time	30

Usage Instructions

Application temperature: +10°C to +80°C. Keep away from all ignition sources. We recommend removing any coarse residues from the surface, applying PETEC Epoxy Primer (Art. No. 71140), and, if necessary, smoothing. Sand the repair area, then thoroughly clean and degrease it using PETEC Silicone Remover (Art. No. 70950). Shake the can well before use (approx. 1-2 minutes) and perform a test spray. Spray the PETEC Primer Filler evenly from a distance of approx. 20 cm on the surface to be coated. We recommend applying 2-3 coats of the product, allowing each coat to air dry for 3-5 minutes before applying the next. Can only be sanded or overcoated with suitable products after it has fully cured (observe the recommended processing times). Before further processing, sand the surface to a matte finish. The sanding grit size must be selected according to the material. Refer to the Technical Data Sheet. Do not use on low-energy plastics (e.g. PE or PP). Always conduct your own tests to ensure that the product is suitable for each application. After use, turn the can upside down and spray until the valve is empty. Ensure adequate ventilation! Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)