

CLEAR COAT

Features

- Protective varnish, UV and weather resistant
- Fast-drying
- Ready-to-use - no mixing required
- High surface hardness with excellent flexibility
- High-gloss finish with excellent flow and levelling
- Excellent polishability
- Excellent adhesion to 1C and 2C paints

Areas of application

The 1-component Clear Coat is a reliable and user-friendly protective coating designed for fast and efficient repair work. It provides excellent adhesion to both 1C and 2C paints. Thanks to its very fine atomization, the clear coat is evenly distributed across the surface, resulting in excellent flow, high sag resistance, and a durable protective finish. This ensures effective sealing against moisture. Its fast drying time and easy application means this durable protective finish is ideal for everyday use in both professional workshops and DIY applications.

TechnicalData

Colours	clear
Shelf life	36 Months

Usage Instructions

Application temperature: +10°C to +80°C. Keep away from all ignition sources. We recommend removing any coarse residues from the surface, applying PETEC Epoxy Primer (Art. No. 71140), and, if necessary, smoothing, PETEC Primer Filler (Art. No. 71240) and painting on top. Thoroughly clean and degrease with PETEC Silicone Remover (Art. No. 70950). Shake the can well before use (approx. 1-2 minutes) and perform a test spray. Spray an even coat of PETEC Clear Coat from a distance of approx. 20 cm on the surface to be coated. We recommend applying 2-3 coats of the product, allowing each coat to air dry for 5 minutes before applying the next. Always conduct your own tests to ensure that the product is suitable for each application. After use, turn the can upside down and spray until the valve is empty. Ensure adequate ventilation! Read the safety and technical data sheet. (Download the PETEC data sheets at www.petec.de)